

Material Safety Data Sheet

MSDS Number: C8001B

Issue Date: 10/1/04

Product Name: Acrylic Sinks made in
Germany by Schock

Revised Date: 11/10/2006

Aristech Acrylics LLC
7350 Empire Drive
Florence, KY 41042

Emergency:
(859) 283-1501 (8 a.m.– 5 p.m. Mon-Fri)
(800) 424-9300 (Off-Hour Emergencies)

Section 1 – Product Identification

Product Name: Acrylic Sinks made in Germany by Schock
Synonyms: Acrylic Sinks
Chemical Name: Polymethylmethacrylate with Alumina Trihydrate as mineral filler

Section 2 – Composition/Information on Ingredients

Ingredient Name	CAS No.	% WT	Exposure Limits
* Acrylic Sinks made in Germany by Schock	Mixture	100	This product can generate Particulates Not Otherwise Regulated (PNOR). The OSHA PEL-TWA for PNOR is 15 mg/m ³ (total dust) and 5 mg/m ³ (respirable fraction). The ACGI TLV-TWA for Particles Not Otherwise Specified (PNOS) is 10 mg/m ³ (inhalable) and 3 mg/m ³ (respirable fraction).
Alumina Trihydrate	21645-51-2	<70	Y(Hazardous)** PNOC - 15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction) (OSHA PEL TWA) PNOC - 10 mg/m ³ (inhalable) 3 mg/m ³ (respirable fraction) (ACGIH TLV TWA)
Polymethyl methacrylate	9011-14-7	>30	N (Hazardous)** N/A – OSHA PEL TWA N/A – ACGIH TLV TWA

*Mixture. Chemicals that follow this listed chemical are part of the listed mixture.

** All ingredients in quantities >1.0% (>0.1% for carcinogens) that are potentially hazardous per OSHA definitions

Some States enforce the PELs that OSHA promulgated in 1989, which were subsequently vacated by the U.S. Supreme Court. Check with your state OSHA agency to determine which PEL is enforced in your jurisdiction.

Section 3 – Hazard Identification

Emergency Overview:

CAUTION! Inhalation of dusts or vapors may cause upper respiratory tract irritation with coughing and a burning sensation in the throat. Repeated skin exposures to dusts may cause allergic skin reactions.

Potential Health Effects:

Material Safety Data Sheet

MSDS Number: C8001B

Issue Date: 10/1/04

Product Name: Acrylic Sinks made in
Germany by Schock

Revised Date: 11/10/2006

Eyes: Transient/mechanical irritation from contact with dusts. Possible irritation from operations and processing vapors or dusts.

Skin: Possible transient/mechanical irritation.

Ingestion: Product in marketed form is inert.

Inhalation: Sawing, sanding, grinding, or burning may cause upper respiratory tract irritation

Relevant Routes of Exposure: Inhalation, eye and skin.

Signs and Symptoms of Acute Overexposure:

Product sold in its marketed form is not expected to present a serious health hazard; however, operations such as sawing, sanding, grinding or burning may generate dust, smoke or vapors which may be irritating. Inhalation of such dusts, smoke and vapors may cause upper respiratory tract irritation. Symptoms may include burning sensation, coughing, sneezing, and sore throat. Skin contact with dust may produce transitory mechanical irritation. Symptoms may include redness and itching. High concentrations of dusts may cause irritation to the eyes causing burning, redness, and tearing. This product is not expected to be toxic if ingested.

Signs and Symptoms of Chronic Overexposure:

Prolonged or repeated over exposures to high concentrations may cause coughing, dizziness, confusion, headache and drowsiness. Prolonged or repeated skin contact may lead to allergic skin reactions.

Medical Conditions Generally Aggravated By Exposure:

Individuals with chronic respiratory disorders may be adversely affected by any fume or airborne particulate matter exposure. Persons with preexisting skin disorders may be more susceptible to the effects of this material.

Carcinogenicity:

NTP: N/A

IARC: N/A

OSHA: N/A

ACGIH: N/A

OTHER: N/A

Additional Information If Applicable

Section 4 – First Aid Measures

Eyes:

Flush immediately with plenty of cool water for at least 15 minutes. Call a physician if necessary.

Skin:

Material Safety Data Sheet

MSDS Number: C8001B

Issue Date: 10/1/04

Product Name: Acrylic Sinks made in
Germany by Schock

Revised Date: 11/10/2006

Wash affected area with soap and plenty of water. If irritation develops, call a physician.

Ingestion:

Product in its marketed form is inert. If large amounts are swallowed, call physician, immediately.

Inhalation:

For overexposure to heated resins, remove from exposure. If breathing is difficult, or has stopped, administer artificial respiration (mouth-to-mouth) or oxygen as indicated. Call a physician, immediately.

Notes to Physicians: None known.

Section 5 – Fire Fighting

Flammable Limits in Air (% by Volume): N/A

Flash Point: N/A

Extinguishing Media:

Use water or dry chemicals to extinguish fire.

Fire Fighting Instructions:

Firefighters should wear NIOSH/MSHA approved self-contained breathing apparatus and full protective clothing when fighting fires. Use cold water spray to cool fire-exposed product.

Unusual Fire and Explosion Hazards:

Burning material may give off toxic products of combustion (CO, CO₂) when involved in a hot fire.

Known or Anticipated Hazardous Products of Combustion:

Combustion products may include carbon dioxide, carbon monoxide, methyl methacrylate monomer (MMA) and acrid smoke and fumes.

Section 6 – Accidental Release Measures

Accidental Release Measures and Methods for Cleanup:

If released or spilled, product may be cleaned up and disposed in the trash. Allow hot or heated material to solidify and cool before disposal.

Section 7 – Handling and Storage

Handling:

Avoid breathing of vapors, fumes and smoke which may be released during thermal processing. Since finished product may have sharp edges, protective gloves should be worn when handling.

Storage:

Material Safety Data Sheet

MSDS Number: C8001B

Issue Date: 10/1/04

Product Name: Acrylic Sinks made in
Germany by Schock

Revised Date: 11/10/2006

Store in cool dry area.

Section 8 – Exposure Controls/Personal Protection

Ventilation Requirements:

Local exhaust ventilation should be used to control the emissions of air contaminants. General dilution ventilation may assist with the reduction of air contaminant concentrations.

Personal Protective Equipment:

Eye/Face:

Employees should be required to wear safety glasses to prevent eye contact when sawing, sanding, drilling and routing.

Skin:

When necessary, garments for protection against heated materials should be used to prevent skin contact with hot acrylate polymer. Since finished material has sharp edges, wear protective gloves when handling.

Respiratory:

Respiratory equipment approved by NIOSH/MSHA for protection against organic vapors and dusts is necessary to avoid inhalation of excessive air contaminants. The appropriate respirator selection depends on the type and magnitude of exposure (refer 29 CFR 1910.134 for appropriate NIOSH approved respirators and to the NIOSH Pocket Guide to Chemical Hazards, DHHS (NIOSH) Publication NO. 2001-145 for equipment selection). Use a positive pressure air supplied respirator if there is a potential for an uncontrolled release, exposure levels are not known or under any other circumstances where air purifying respirators may not provide adequate protection.

Other Protective

Clothing/Equipment:

Emergency eye wash stations and safety showers should be available in the work area.

Section 9 – Physical/Chemical Properties

Appearance: Solid sheets and shapes, various colors

Boiling Point: N/A

Molecular/Chemical Formula: N/A

Evaporation Rate: N/A

Bulk Density: N/A

Freezing Point: N/A

Melting Point: N/A

Octanol/Water Partition Coefficient: N/A

Water/Oil Distribution Coefficient: N/A

Odor: Odorless

Odor Threshold: N/A

Percent Volatile: N/A

pH Value: N/A

Physical State: Solid sheet and shapes

Reactivity in Water: N/A

Material Safety Data Sheet

MSDS Number: C8001B

Issue Date: 10/1/04

Product Name: Acrylic Sinks made in
Germany by Schock

Revised Date: 11/10/2006

Solubility in Water: Insoluble

Specific Gravity or Density(Water=1): 1.6-1.8

Vapor Density: N/A

Vapor Pressure: N/A

Section 10 – Stability/Reactivity

Stability:

Stable

Conditions to Avoid:

Temperatures above 500 Deg. F (260 Deg. C) can release methyl methacrylate.

Incompatibility With Other Materials:

None known.

Hazardous Decomposition Products:

Carbon dioxide, carbon monoxide, acrid smoke and fumes, possibly Methyl methacrylate

Hazardous Polymerization:

Will not occur

Conditions to Avoid:

None known.

Section 11 – Toxicological Information

VALUE	ANIMAL	ROUTES	COMPONENTS
LC ₅₀ : 7093	Rat	Inhalation	Methyl methacrylate
LD ₅₀ : 7900	Rat	Ingestion	Methyl methacrylate
LD ₅₀ : >33,500	Rabbit	Absorption	Methyl methacrylate

Toxicological Information:

Product Based Information:

No toxicological information is available for the finished product. This product is generally believed to be inert based on available data.

Ingredient Based Information:

Alumina trihydrate may cause eye and skin irritation.

The monomer of polymethyl methacrylate is methyl methacrylate (MMA). In one study, high doses of MMA were reported to produce an increased incidence of blood vessel aggregates in rat pups whose mothers received MMA by injection while pregnant.

Degenerative changes in the liver were observed in Guinea pigs following inhalation exposure to 9.5 ppm of MMA for 3 hours/day for 15 days, according to a 1945 report.

Material Safety Data Sheet

MSDS Number: C8001B

Issue Date: 10/1/04

Product Name: Acrylic Sinks made in
Germany by Schock

Revised Date: 11/10/2006

Ingestion of MMA caused irritation of the alimentary canal and kidney and liver lesions (Lefaus, R. Practical Toxicology of Plastics. CRC Press, Inc., 1968P.324). Methyl methacrylate has been shown to cause neurotoxic effects in primarily animal studies.

Carcinogenicity: None of the ingredients listed in Section 2 are considered carcinogens by OSHA, NTP, or IARC.

Possible target organs: Skin and respiratory system (e.g., lungs)

Additional Information If Applicable

Section 12 – Ecological Information

Ecological Information:

No ecological data are currently available.

Additional Information If Applicable

Section 13 – Disposal Considerations

Disposal Considerations: Dispose of in accordance with local, state and federal requirements. This product as sold in its marketed form is not considered an EPA hazardous waste when discarded.

Additional Information If Applicable

Section 14 – Transport Information

Proper Shipping Name: Not regulated as a hazardous material

Hazard Class: none

ID Number: none

Packing Group: none

Additional Information If Applicable

Section 15 – Regulatory Information

U.S. Federal Regulations:

Toxic Substances Control Act (TSCA) Inventory- Yes

Superfund Amendments and Reauthorization Act (SARA 313)- N/A

State Regulations:

California Proposition 65 List.

This product does not any chemicals listed by the State of California to cause cancer and/or birth defects or other reproductive harm.

International Regulations:

European Inventory (EINECS)- Unknown

Material Safety Data Sheet

MSDS Number: C8001B

Issue Date: 10/1/04

Product Name: Acrylic Sinks made in
Germany by Schock

Revised Date: 11/10/2006

Canadian Inventory (DSL)- Yes

SARA Hazards:

Acute: Yes **Chronic:** No

Reactive: No **Fire:** No

Pressure: No

Additional Information If Applicable

Section 16 – Other Information

NFPA Codes:

Health: 2

Flammability: 0

Reactivity: 0

HMIS Codes:

Health: 1

Flammability: 0

Reactivity: 0

Other Information:

If you require additional information regarding any legal or regulatory requirements referred to in this MSDS, we suggest that you consult with an appropriate regulatory agency, or with a professional with expertise in this area.

This information is taken from sources or based upon data believed to be reliable; however, Aristech Acrylics LLC makes no warranty as to the absolute correctness or sufficiency of any of the foregoing or that additional or other measures may not be required under particular conditions.

Additional Information If Applicable

Reason for MSDS Revision: EH&S Review

This MSDS was prepared in accordance with the ANSI Z400.1 1993 Guideline for the Preparation of Material Safety Data Sheets.

KEY

N/A= Not Applicable

MSHA=Mine Safety and Health Administration

NIOSH=National Institute of Occupational Safety and Health

SARA= Superfund Amendment and Reauthorization Act

CNS= Central Nervous System

ACGIH=American Conference of Governmental Industrial Hygienists

OSHA=Occupational Safety and Health Administration

PNOC=Particulates Not Otherwise Classifiable

TLV=Threshold Limit Value

PEL=Permissible Exposure Limit

TWA=Time Weighted Average

STEL=Short Term Exposure Limit

CEIL=Ceiling Limit Value

For additional product information, please call 800-354-9858.